## 760240957 | 30" Pole Cab with Round Shaft



Bottom of the Pole, 30in Square 4G/5G capable Concealment Enclosure to house and conceal multiple low to high power radios and any other wireless infrastructure equipment in a cabinet at the base of the pole.

- Intended to house and conceal multiple radios and any other wireless infrastructure equipment in a cabinet at the base of the pole
- Flexible configuration accepts low to high-power single or dual band radios, Integrated AC load center/OVP and Disconnect and integrated AC/DC rectifier options

Available with Pole Top concealment, mmWave 5G mounting, luminaire arms.

Available After Market Kits -- ordered separately:

- 860665491-AMK-001 - Ericsson 4480/4415/8863 Radios & 6304 PSU Mounting Kit

#### **Product Classification**

Portfolio CommScope®

Product Type Pole cab
Product Brand Metro Cell

Ordering Note CommScope® standard product with terms

**Warranty** One year

### General Specifications

**Color** Light Gray (RAL 7035)

Color Options Beige-Grey (RAL 7006) | Black (RAL 9005) | Black Green (RAL 6012) | Brown (RAL 8014) | Faux

Concrete | Green (RAL 6005) | Metallic Silver | Umbra Grey (RAL 7022)

**Compatible Foundation Type** Poured Concrete | Pre-Cast Concrete

**Cooling** Fan Cooling

Power Supply Compatibility 6302 | DELTA 2.0 | PSU-AC-08

**Radio Compatibility, Ericsson** 1281 | 220x | 440x | 4415 | 4426 | 4449 | 4478 | 4480 | 6701 | 8843 | 8863 | Diplexer

Radio Compatibility, Nokia (2) Airscale dual band radios (160W or 320W and (2) Delta 1kW rectifiers (base) | AEUB | AEWB | AEWD

/AEWE | AHBCA | AHFIA | AHFIB | AHFIC | AHIA | AHIB | AHLBA | AHLBBA | AZRB | Diplexe

Radio Compatibility Samsung AT1K01 | AT1K02 | AT1K0X | Diplexer | RF4402D-D1A | RFV01U-D1A | RFV01U-D2A | RT2201-

46A | RT4401-48A

Radios Included None

Dimensions

**COMMSCOPE®** 

# 760240957 | 30" Pole Cab with Round Shaft

**Height Note** 4 ft tall Equipment Cabinet Base

**Pole Height Options** 10.668 m | 35 ft | 12.192 m | 40 ft | 6.096 m | 20 ft | 7.62 m | 25 ft | 9.144

m | 30 ft

 Width
 762 mm | 30 in

 Depth
 762 mm | 30 in

**Depth Note** Square

Pole Diameter 203.2 mm | 8 in

**Electrical Specifications** 

Input Voltage230-115 VacGenerator ConnectionNo connection

**Power/Fiber Input**AC load center with OVP and disconnect

Material Specifications

Finish Aluminum Chromate

Finish Concealment Covers Powder coated

Material Type Steel

## **Environmental Specifications**

Thermal Compliance GR-487

### \* Footnotes

Warranty For more information, please consult our Product Warranty guidelines

**Pole Height Options** Overall AGL Standard Height

