

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © 2016 Commscope, INC. Confidential NOTICE: These drawings and specifications are the proprietary property of COMMSCOPE, INC. and may be used only for the specific purpose authorized in writing by COMMSCOPE, INC.

REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
C		ENC 8000017781-REBRANDING	11 29 16	SC	RC



NOTES:

- 1 ATTENUATION ≤ 0.15 dB, MEASURED AT 850 nm ACC. TO I.E.C. 61300-3-4 INSERTION METHOD B WITH MODAL CONDITION ACCORDING TO IS 14763-3, OFSTP-14, IEC 61280-4-1
- 2 RETURN LOSS ≥ 35 dB, IN MATED CONDITION AGAINST REFERENCE CONNECTOR AT 850 nm
- 3 TEST RESULT SHEET SUPPLIED WITH EACH INDIVIDUALLY PACKED ASSEMBLY
- 4 INFO ON LABEL INSIDE THE BAG:
 - BARCODE
 - UNIQUE SERIAL NUMBER
 - COMMSCOPE PART NUMBER
 - LENGTH
 - FACTORY ORDER NUMBER
 - MAX. IL / MIN RL VALUE
- 5 CABLE INFORMATION:
 - CORE DIAMETER: 50/125 μ m
 - OUTER JACKET DIAMETER: 0.9 mm SEMI-TIGHT
 - OUTER JACKET COLOUR: AQUA
 - OUTER JACKET MATERIAL: LSZH

PART NUMBER	"L" (meter)
2160042-2	2.0 -0/+0.1

1	FOAC INFORMATION LABEL	-
1	LC CONNECTOR, HIGH CONNECTIVITY	2
L	FOCAB 0,9S 50/125 OM4 AQUA LSZH	1
Qty	Description	Item
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 20-01-2011 M.A.H. Oppers
DIMENSIONS: mm		CHK 20-01-2011 T.v.d. Meulen
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 20-01-2011 M.A.H. Oppers
0 PLC $\pm -$		PRODUCT SPEC
1 PLC $\pm -$		APPLICATION SPEC
2 PLC $\pm -$		
3 PLC $\pm -$		
4 PLC $\pm -$		
ANGLES $\pm -$		
FINISH		
MATERIAL		WEIGHT -
CUSTOMER DRAWING		SCALE NTS
SIZE A2		CAGE CODE -
DRAWING NO C=2160042		RESTRICTED TO -
SHEET 1 of 1		REV C

2160042