


# CAF-7C7C-LSON

---



Armored Jumper G657.A2 LC/APC to LC/APC Duplex, 3.0mm LSZH, Yellow

## Product Classification

<b>Regional Availability</b>	Asia   Australia/New Zealand   China   India
<b>Portfolio</b>	CommScope®
<b>Product Type</b>	Fiber patch cord, duplex

## General Specifications

<b>Connector A, quantity</b>	2
<b>Color, boot A</b>	Green
<b>Color, connector A</b>	Green
<b>Connector B, quantity</b>	2
<b>Color, boot B</b>	Green
<b>Color, connector B</b>	Green
<b>Construction Type</b>	Armored
<b>Interface, Connector A</b>	LC/APC
<b>Interface, Connector B</b>	LC/APC
<b>Jacket Color</b>	Yellow
<b>Polarity</b>	Pairs, flipped
<b>Total Fibers, quantity</b>	2

## Dimensions

<b>Cable Assembly Length Range (m)</b>	1 – 300
<b>Cable Assembly Length Range (ft)</b>	3 – 999
<b>Diameter Over Jacket</b>	3 mm   0.118 in

## Mechanical Specifications

<b>Tensile Load, long term, maximum</b>	200 N   44.962 lbf
<b>Tensile Load, short term, maximum</b>	400 N   89.924 lbf

# CAF-7C7C-LS0N

---

**Cable Retention Strength, maximum** 15.43 lb @ 0°

## Optical Specifications

**Fiber Mode** Singlemode  
**Fiber Type** G.657.A2, TeraSPEED®  
**Insertion Loss, maximum** 0.25 dB  
**Return Loss, minimum** 60 dB

## Environmental Specifications

**Operating Temperature** -25 °C to +70 °C (-13 °F to +158 °F)  
**Environmental Space** Low Smoke Zero Halogen (LSZH)  
**Qualification Standards** IEC 61753-1, category OP

## Packaging and Weights

**Packaging quantity** 1